



Applied Security Design Ltd.

Utility Range Apollo mini Pizza



- ◆ Suitable for internal or external use
- ◆ IP65 Rating
- ◆ Complete with energy saving lamps
- ◆ Photocell option (External use only)
- ◆ High frequency versions
- ◆ Phase correction available on request
- ◆ Rated for continuous use
- ◆ Anti-tamper screws available on request

All the products have been manufactured to the highest standards are both 'CE' and 'F' marked and conform to the latest British and European standards

A slim-line polycarbonate circular fitting with screw down cover.

Available in a choice of colours with prismatic or opal diffuser

Rated at IP65, suitable for use with energy saving 16W, single or twin 9W PL lamps, giving a saving of up to 80% on conventional lighting.

Technical Specifications

Mains Supply	230V~50Hz	Gear tray	Pre-coated steel.
Lamps	16W 2D Single or 2 X PL9	Cable entry	Single 20mm grommet on rear of base, 2 x 20mm side knock outs and Besa box
Unit diameter	205mm	Photocell switching level	100 Lux (Approx)
Unit height	81mm	Standard	Conforms to BS EN60 598-2-1
Material	Polycarbonate	HF Frequency	47kHz
Protection rating	IP65	Emergency options	16W Non Maintained integral 16W Maintained ext batt pack
Running current standard	Single PL9 = 160mA Twin PL9 = 160mA 16W 2D = 200mA	Running current phase corrected	Single PL9 = 71mA Twin PL9 = 71mA 16W 2D = 90mA