



Applied Security Design Ltd.

Utility Range

Apollo Pizza



- ◆ Suitable for internal or external use
- ◆ IP65 Rating
- ◆ Complete with energy saving lamps
- ◆ Photocell option (External use only)
- ◆ Rated for continuous use
- ◆ High frequency versions
- ◆ Phase correction available on request
- ◆ Anti-tamper screws available on request

All the products have been manufactured to the highest standards are 'CE' and 'F' marked and conforms to the latest British and European standards

A slim-line polycarbonate circular fitting with a screw down cover.

Available in a choice of colours with prismatic or opal diffuser.

Rated at IP65, suitable for use with energy saving lamps (single or twin 11W PL lamps available upon request) giving a saving of up to 80% on conventional lighting. Also available is a High frequency option.

Technical Specifications

Mains Supply	230V~50Hz	Cable entry	20mm side knock outs and grommet
Lamps	28W & 38W 2D	Standard unit	Conforms to BS EN60 598-2-1
Unit diameter	286mm	Emergency unit	Conforms to BS EN60 598-2-22
Unit depth	81mm	Photocell Switching level	100 Lux (Approx)
Material	Polycarbonate	Protection rating	IP65
Gear tray	Pre-coated steel.	HF frequency	47kHz
Running current standard	28W = 320mA 38W = 430mA	Running current phase corrected	28W = 155mA 38W = 210mA
Ballast lumen factor 28W emergency unit	Mains 0.75 Emergency 0.18		