



18AS2

DINRAIL, ROWBOARD, SERVICE CENTRES

Rowboard:

- Suitable for 'Stand-Alone' use or 'Add-On' above Standard 'L' type board.
- Each row will accommodate 18 off 18mm module wide DIN Rail mounted devices.
- Main Neutral and Earth Bars included, along with provision for additional 'Mini' Neutral and Earth bars.

No of Rows	Surface	Flush
1	18AS1	18AF1
2	18AS2	18AF2
3	18AS3	18AF3
4	18AS4	18AF4
5	18AS5	18AF5



18DIN18

Service Centre/DIN Rail Board:

- Suitable **only** for fixture above Standard 'L' Type board.
 - Equipped with easily removed DIN Rail to accommodate 18 or 36, 18mm module wide DIN Rail mounted devices.
- See page 114 for DIN Rail Control Devices

18 Module	18DIN18
36 Module (2 Rows of 18)	18DIN36

Cable Spreader Box

Add on Enclosure, 243mm high, Blank front cover plate	18SB
---	-------------



125SW3

125SW4

LOADSTAR STANDARD 'L' BOARD: INCOMING OPTIONS

Order Device and Kit (where required) separately.

Switch Disconnector, modular (50mm ²)	Device	Kit
40A TP	40SW3	
63A TP	63SW3	None
100A TP	100SW3	Required
125A TP	125SW3	
40A 4P	40SW4	18LK125
63A 4P	63SW4	18LK125
100A 4P	100SW4	18LK125
125A 4P	125SW4	18LK125



18LKD50

18R100/30/4

RCCB (50mm ²)	Device	Kit
40A 4P 30mA	18R40/30/4	18LK125
100mA	18R40/100/4	18LK125
300mA	18R40/300/4	18LK125
63A 4P 30mA	18R63/30/4	18LK125
100mA	18R63/100/4	18LK125
300mA	18R63/300/4	18LK125
100A 4P 30mA	18R100/30/4	18LK125
100mA	18R100/100/4	18LK125
300mA	18R100/300/4	18LK125



18LK125



18LKD70 (fitted)

Direct Connection	Device	Kit
Incoming Cable Connection (50mm ²)	18LKD50	None
Outgoing Cable Connection Kit/Shroud (70mm ²) (Set of 3 Cable Clamps + Shroud)	18LKD70	Required