



18LS08



18LF08



18LS08D

LOADSTAR STANDARD 'L' BOARD 125A MAX INCOMER

No of Ways	Surface	Flush
4	18LS04	18LF04
6	18LS06	18LF06
8	18LS08	18LF08
12	18LS12	18LF12
16	18LS16	18LF16
20	18LS20	18LF20
24	18LS24	18LF24

- Incoming options - order separately:
125A Switch Disconnecter TP/4P - 50mm²
100A RCCB 4P - 50mm²
Direct Cable - 50/70mm²
- Busbars rated 200A
- Full compliment of Neutral and Earth terminals plus spares:
Incoming maximum 70mm²
Outgoing maximum 25mm²
- Facility included to allow fixture of Double Earth bars - High Integrity Earth to regulation 607 section 543
- Clean Earth kit available
- All boards supplied as standard with hinged outer door and catch - lock extra - and removable top/bottom gland plates

ADD-ON 12 WAY LOADSTAR 'L' BOARD

No of Ways	Surface
12	18LS12A
Vertical Connection Kit (Inc. conns.)	18LK12V

- 18LS12A 'Add-on' Board is designed to fit above 16, 20 & 24 way 'L' Boards, to create 28, 32 & 36 way TP Boards
- 18LK12V kit connects 18LS12A to 16, 20 & 24 way Boards

LOADSTAR 'L' BOARD METER PACK

An 'Add-on' Assembly, 245mm high, to be fitted below an 'L' Board, comprising Enclosure with slotted front plate and hinged door, Digital meter, pulsed output, offering Amps, Volts and Kwh readout, 3 off current transformers, 125A with associated fuses and wiring.

	LIST No
125A CTs	18ML125

LOADSTAR BOARD 125A WITH INTEGRAL DIN RAIL

No of Ways	Surface
4	18LS04D
8	18LS08D
12	18LS12D
16	18LS16D
20	18LS20D

All the facilities of the Standard board above, plus:

- DIN rail to accommodate up to 18 modules of control devices - Contactor, Timer etc.
- DIN Rail easily removed to assist cabling.
- All devices - incomer, MCBs & Control equipment - behind common front plate and outer door.

LOADSTAR IP66 125A BOARD

No of Ways	H	W	D	Surface
4	800	500	215	IP18LS04
6	800	500	215	IP18LS06
8	800	500	215	IP18LS08
12	1000	500	215	IP18LS12
16	1200	500	215	IP18LS16

Boards consist of IP66 steel enclosure door, with 'L' Board interior. Incomer, kit and MCB extra as for 'L' Boards above.