



KLED09STD

9w LED DD Standard, 30000hrs



Product Overview

Kosnic's range of LED DD lamps takes a fresh approach to functional lighting with a design philosophy offering plug-in emergency packs and optional microwave sensor versions so that there are no barriers to retrofitting LEDs in commercial fittings. The products bring the energy saving capabilities of LED technology to the commercial environment and the lamps can quickly replace fluorescent DD lamps with little or no rewiring.

Features

Save energy up to 65% compared with a fluorescent DD lamp with magnetic ballast.

For maximum energy savings, bypass all control gear and supply directly from the mains.

Single side high lumen output for light only where it's needed.

Long life of 30,000h.

Compatible with Kosnic's KTC27EME-DD emergency module.

Instant start.

Negligible UV output.

Mercury free.

Emergency Module Compatible

The LED DD lamp is compatible with the Kosnic emergency module, which provides power in the event of a cut in the supply and must be wired to an un-switched supply. The battery will supply the lamp for over 3 hours at a reduced output.

Safety and Maintenance

Switch off supply and allow cooling before handling lamp.

Do not dispose of in household waste.

Dispose of in appropriate section of local civic amenity site or recycling centre.

Specifications

	KLED09STD/2P-W40	KLED09STD/4P-W40
Fitting	2-Pin (GR8)	4-Pin (GR10q)
Shape / Type	DD	DD
Colour Finish	White	White
Wattage (w)	9	9
Total Lumens (lm)	1050	1050
Input Current (mA)	43	43
Input Voltage	220-240Vac	220-240Vac
CCT Temperature (k)	4000	4000
CCT Name	Cool White	Cool White
Rated Life (hrs)	30000	30000
Nominal Lifetime (hrs)	30000	30000
Switch Cycles	50000	50000
Peak Candelas (cd)	350	350
CRI	83	83
Dimmable?	No	No
Retrofit?	Yes	Yes
Power Factor	0.9	0.9
Start Time (s)	0.39	0.39
Warm-up Time (s)	Instant full light	Instant full light
Length (mm)	145	145
Width (mm)	145	145
Depth (mm)	30	30
Mercury (mg)	0	0
Clean-up instructions	N/A	N/A

Unit D2 Kennetside, Bone Lane
NEWBURY, BERKSHIRE

T: 01635 523 713 E: sales@kosnic.com W: <http://www.kosnic.com>

Rated Power (W)	9.00	9.00
Rated Luminous Flux (lm)	1050	1050
LMF at Lifetime	0.75	0.75
SDCM of CCT	<6	<6
Ambient Temperature (°C)	-20 to 40	-20 to 40
Emergency Luminous Flux	230	230

Product Markings

	KLED09STD/2P-W40	KLED09STD/4P-W40
Manufacturer	Kosnic	Kosnic
Product Code	KLED09STD/2P-W40	KLED09STD/4P-W40
Voltage	220-240Vac 50-60Hz	220-240Vac 50-60Hz
Nominal Power (W)	9	9
Current (mA)	43	43
CE Mark	Yes	Yes
WEEE Mark	Yes	Yes
Batch Code	Yes	Yes

Energy Label


	KLED09STD/2P-W40	KLED09STD/4P-W40
Manufacturer	Kosnic	Kosnic
Product Code	KLED09STD/2P-W40	KLED09STD/4P-W40
Energy Class	A++	A++
Energy Consumption (kWh/1000h)	9	9

Unit D2 Kennetside, Bone Lane
NEWBURY, BERKSHIRE


T: 01635 523 713 E: sales@kosnic.com W: <http://www.kosnic.com>

Packaging

	KLED09STD/2P-W40	KLED09STD/4P-W40
UPC Code	5060063420707	5060063420714
Outer Box Length (mm)	455	455
Outer Box Width (mm)	415	415
Outer Box Height (mm)	270	270
Volume	0.05098275	0.05098275
Box Quantity	20	20
Outer Box Weight/kg	3.9	3.9



KLED09STD/2P-W40
KLED09STD/4P-W40



Datasheet generated from <http://www.electrika.com> last updated Friday, August 18, 2017 12:54:28 PM