

DATA SHEET:

LEDBAT Series

Knightsbridge[®]
the mark of quality

ISSUE: BADEC16VOL1

LED Batten



| MLA part code | LEDBAT9 | LEDBAT17 | LEDBAT22 | LEDBAT26 |
|--|--|---|---|---|
| Description | LED Batten | | | |
| ErP Class | A+ | | | |
| Nett Weight (kg) | 0.21 | 0.35 | 0.43 | 0.48 |
| Total wattage (W) | 8.86 | 17.11 | 22.05 | 51.75 |
| Lumens (lm) | 900 ± 5% | 1800 ± 5% | 2400 ± 5% | 5350 ± 5% |
| Efficacy (lm/W) | 101 | 105 | 108 | 103 |
| P.F | >0.9 | | | |
| Beam Angle (°) | 150 | | | |
| Overall dimensions (mm) | Length: 605 Width: 30 Projection: 45 | Length: 1220 Width: 30 Projection: 45 | Length: 1520 Width: 30 Projection: 45 | Length: 1768 Width: 30 Projection: 45 |
| CCT | 4000K | | | |
| LED Colours | Cool White | | | |
| CRI | >80 | | | |
| LED type | SMD | | | |
| Operating current (A) | 0.042 | 0.081 | 0.105 | 0.118 |
| Input voltage | Mains 230V 50Hz | | | |
| Construction | Aluminium & Polycarbonate | | | |
| Class | Class II | | | |
| IP rating | IP20 | | | |
| Warranty | 3 Year | | | |
| Additional Accessories available | N/A | | | |
| Photometric data | Yes | | | |
| Dimmable | No | | | |
| Origin of Manufacture | China | | | |
| Quality assurance system | ISO9001 | | | |
| Declaration of Conformity (held on file) | Yes | | | |
| Manufactured & accordance with | BS EN60598 | | | |
| EAN | 5055832960683 | 5055832960904 | 5055832960911 | 5055832959915 |

