

Product Description:

The IP65 driverless range of QuaZar™ floodlights incorporate the latest in high voltage LED technology. With their ultra slim profile and high performance, now you can light your external areas and gardens without sacrificing the appearance. Available in 10W, 20W, 30W and 50W versions.

Product Image:




Product Features:

- IP65 rated LED floodlight with ultra slim design for minimal visual impact
- IK08 rated aluminium housing and tempered glass provides excellent protection
- Available in black and white finish housing
- Pre-wired with 800mm of cable
- 1.5kV surge protection
- 3 year warranty

30W Adjustable IP65 Driverless LED Floodlight

Line Drawing Image



Product Specs:

Technology	LED	Number of LEDs	42
Luminaire Distribution	Direct	Lifetime L70 (hrs)	25000
Input Voltage	180~265V AC	Input Frequency	50/60HZ
Dimmable	No	Dali	No
IP Rating	IP65	IK Rating	IK06
Operating Temp. (Max) C	40	Power Factor	0.9
Lamp Base	None	Height (mm)	155
Width (mm)	200	Surge Protection (kV)	1.5

SKU Table and Ordering

SKU Code	Colour	Lumens/Watt	Wattage	Lumens	Beam Angle	Ra
EN-FLH30BLK/40	4000	90	30	2700	120	70
EN-FLH30W/40	4000	90	30	2700	120	70

Compliance & Approvals:



Warranty

This product has a warranty period of 3 Years.

Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

UK Enlite Sales & Distribution
Apex Park
6 Little Burrow
Welwyn Garden City AL7 4SW
United Kingdom
Tel : +44 (0) 1707 35 18 20