

FireAngel

WHT-630T

10 Year Life THERMISTEK Wireless Interlink Heat Alarm

Wi-Safe[®] 2 Wireless Interlink

THERMISTEK[™]



10 year sealed in power pack
removes the need to replace the batteries

Diameter 132mm

Height 60mm

Weight 204g



Common features

- Thermistek predictive technology monitors the rate of temperature increase and alerts you to the danger quicker. Thermistor heat sensing element for accuracy, reliability and stability.
- 10 year sealed for life battery.
- Wirelessly interlink up to 50 Wi-Safe 2 smoke, heat, CO alarms and accessories on a single network.
- Single button provides 'test' and 'silence' functions.
- Optional locking mechanism on installation.
- Class A1 fire detection (54°C - 65°C).
- Locate feature – When a network of alarms goes into alarm pressing the test button on any of the units will silence all but the initiating alarm.
- Heat alarms are for use in places where a smoke detector is not suitable, for example where there are high ambient air temperatures, high humidity or in dusty and dirty environments. eg: garages, lofts and kitchens.



KM607094
BS 5446-2:2003



Technical specification

Power	10 year sealed lithium battery
Technology	Thermistek and Wi-Safe 2
Alarm sound level	85dB at 3m
Operation	DC
Installation positions	Ceiling
Operating temperature	Class A1, 54°C - 65°C
Operating humidity	Up to 90% RH% non-condensing
Storage temperature	-20°C to 60°C
Storage humidity	Up to 93% RH non condensing
Warranty	5 years
Master pack quantity	10
Approvals	Third party certified to BS 5446-2:2003 by BSI
Max No. of connected units (network)	50 units
Networking	Multi-directional communication
Compatibility	Compatible with all products containing Wi-Safe 2, including use in mixed systems (ie of mains and battery powered products).
Independently tested	RF standard ETSI EN 300 220-2 V2.3.2 (2010-02) by TRaC
Range	35m (over 200m in clear air)
EAN	0816317002916
Packaging	Full colour printed cardboard box, in outer boxes of 10

FOR FURTHER INFORMATION OR SALES ENQUIRIES:
Tel +44 (0) 2477 717 700 Email sales@sprue.com Website sprue.com

