



ASWTLED/3M

Swift LED Bulkhead Maintained / Non-Maintained 3W White



Features

Small and unobtrusive LED bulkhead.

Supplied with self-adhesive legend.

Optic design provides optimum performance for escape route lighting.

Side and rear cable entries.

Screwless gear tray for ease of installation.

Viewing distance 17 metres.

General Information

Lamp Type	LED
Colour / Finish	White
IP Rating	IP65
Class Protection	1
Internal / External	Internal/External
Surface / Recessed / Suspended	Surface
Warranty (Years)	3
CE Mark	Yes
Height / Depth	40
Length / Diameter	210
Width	100
Accessories	ASBP/1

Technical Information

Wattage	3W
Lumens Delivered	69lm (Emergency), 163lm (Standard)
CCT	6500K
Input	230V
Hertz	50/60Hz
Operating Temp	0C° to 45C°

Technical Data - ETIM 6 - Emergency luminaire (EC001957)

Mounting method	Wall surface mounted
With light source	Yes
Lamp power	3 W
Colour housing	White
Type of indicator	Only single-sided
Labelling type	Sticker
Voltage type	AC
Nominal voltage	230-230 V
Protection class	I
Degree of protection (IP)	IP65
Length	210 mm
Width	100 mm
Height/depth	40 mm
Luminous flux at emergency operation	94 lm
Recognition distance	17 m
Rated luminous flux acc. IEC 62722-2-1	147 lm
Colour of light	White
Colour temperature	6500-6500 K

Datasheet generated from <http://www.electrika.com> last updated Monday, September 3, 2018 2:36:49 PM

