



EESN0105S65

IP65 LED Emergency Exit Sign or Emergency Bulkhead Luminaire



Product Overview

Kosnic's LED Emergency Exit Sign or Emergency Bulkhead Luminaire is a self-contained, multi-purpose, non-maintained or maintained 3-hour emergency exit sign or emergency luminaire solution. The fitting can be used with or without the emergency exit graphics. It is supplied with adaptable self-adhesive graphics that can be arranged to indicate escape routes as necessary.

Features

Three hour rated duration

Class II, IP65

Self-adhesive graphics (1 x right figure, 1 x left figure, 2 x direction arrows)

Surface mounting

Conduit entry

Polycarbonate

Ni-CD battery

Mercury free

Unit D2 Kennetside, Bone Lane

Newbury, Berkshire

T: 01635 523 713 E: sales@kosnic.com W: <http://www.kosnic.com>

Specifications

Shape / Type	Bulkhead
Colour Finish	White
Power (W)	5
Total Lumens (lm)	190 (without Graphics) 70 (with Graphics)
Input Current (mA)	46
Input Voltage	220-240 Vac 50-60 Hz
CCT Temperature (k)	6500
CCT Name	Day Light
Rated Lifetime (hrs)	30000
Beam Angle (°)	120
Power Factor	0.47
IP Rating	IP65
Class Protection	Class II
Warm-up Time (s)	Instant full light
Mounting	Surface mounting with 20mm knock-out on each side. Twin push-fit terminals.
Width (mm)	
Height (mm)	114
Depth (mm)	352
Diameter (mm)	56
Mercury (mg)	0
LMF at Lifetime	0.75
Ambient Temperature (°C)	-20 to 40
Emergency Conversion Time (seconds)	1
Emergency Operating Time (hours)	3
Battery Code	KBAT1500NC9

Unit D2 Kennetside, Bone Lane
Newbury, Berkshire

T: 01635 523 713 E: sales@kosnic.com W: <http://www.kosnic.com>

Battery Voltage (V)	3.6
Battery Capacity (mAh)	1500
Battery Type	Nickel Cadmium
Battery Life (years)	4
Charging Time (hrs)	12
Emergency Operation Test	Manual
Barcode	5060063429885



