





a warmth for every season

EZEMAT 160W 240V
EZEMAT 200W 240V



Description

The Ezewarm Tile Heating Mats comprise of free running, high tensile, multi - stranded, insulated resistance heating wire laid directly under the finished floor surface. The cable is attached to a tough fiberglass mesh which facilitates easy installation. The mats have double-sided tape for secure installation.

Product Construction

The tile heating mat is manufactured using dual core heating element and tough fibreglass mesh. Our heating element has been approved by TUV Rheinland and America's UL (Underwriters EN 60335-2-96 Laboratories). Each heating mat is individually subjected to rigorous safety checks.

Ezemat Systems 160w				Ezemat Systems 200w			
Heated Area	Wattage (W)	Amps	Resistance Ohms	Heated Area	Wattage (W)	Amps	Resistance Ohms
1	160	.67	360	1	200	0.83	288
1.5	240	1	240	1.5	300	1.25	192
2	320	1.33	180	2	400	1.67	144
2.5	400	1.67	144	2.5	500	2.08	115.20
3	480	2	120	3	600	2.50	96.00
4	640	2.67	90	4	800	3.33	72.00
5	800	3.33	72	5	1000	4.17	57.60
6	960	4	60	6	1200	5.00	48.00
7	1120	4.67	51.43	7	1400	5.83	41.14
8	1280	5.33	45	8	1600	6.67	36.00
9	1440	6	40	9	1800	7.50	32.00
10	1600	6.67	36	10	2000	8.33	28.80

Technical Specification

- Operating Voltage: 220-240V. 50Hz
- Width: 500mm (0.5 metre)
- Mat thickness: 3mm
- Primary Cable Insulation: ETFE Fluoropolymer
- Power Output Rating: 160w or 200w per m2
- Power Lead: 3m long braided connection lead
- Lifetime warranty and no quibble installation guarantee.

free phone 0800 644 0181

www.ezewarm.com | www.ezewarm.co.uk

enquiries@ezewarm.co.uk

