



Combined Door Contact/Shock Sensor

Combined Door Contact/Shock Sensor

Two modes of detection in one

The DET-RDCS combines a radio door contact and shock sensor to provide the convenience of two modes of detection in one unit. Activation of either or both units provides an unconfirmed alarm condition.

Single housing to speed up installations

Enable two types of detection for any door or window

Fully compatible with all product ranges

The DET-RDCS is also compatible with the new Menvier and i-on ranges.



Technical Specification

Product name	DET-RDCS (DET-RDCS-B in brown)
PD6662:2010	Security Grade 2
Environmental	Class II
Operating temperature	-10 to +55°
Humidity	0-93% RH Non condensing
Dimensions	Main unit: (L) 118 x (W) 30 x (H) 27mm, Contact: (L) 40 x (W) 11 x (H) 8mm
Weight	46g (with battery fitted)
Battery type	CR2
Voltage	3V
Expected battery life	Two years
Radio operating frequency	868.6625MHz Narrowband
Transmitter range	Up to 1000m in free space, depending on conditions and receiver
Compatibility	All Cooper Security 868MHz radio receivers

Note: This unit alone cannot deliver a confirmed alarm

For consumer literature or more information please contact
Touchpoint Member Services

telephone: +44 (0)1594 541 979
email: touchpoint@coopersecurity.co.uk

Supported by
touchpoint



Low Energy

DET-RDCS-1/1



www.coopersecurity.co.uk

All Cooper logos are valuable trademarks of Cooper Industries in the U.S and other countries. You are not permitted to use Cooper trademarks without the prior consent of Cooper Industries.

COOPER Safety