

## Undersink installation

### Economical and elegant.

---

The small water heaters for undersink installation make their case in many ways. They are equipped with a variable temperature selection from 35 °C and 85 °C, enabling water to be drawn at all times at the same temperature. The optional temperature limits at 38, 45, 55 or 65 °C act as anti-scalding settings or can be used as economy settings. With the SNU 5 SL anti-drip-comfort, the anti-drip function prevents the tap from dripping during heating up, which in turn prevents scale deposits and saves water. Furthermore, the Thermostop function prevent heat from being radiated via the mixer tap in standby when operating the SNU 5 SL anti-drip-comfort, SNU 10 SL comfort and the UFP 5 t.



### The most important features

Anti-drip function 5 SL

Thermostop function of the SNU 5 SL, SNU 10 SL comfort and the UFP 5 t

Water heater with 5 or 10 litres capacity (subject to model)

1.0 or 2.0 kW (subject to model)

Low standby loss power consumption

For a single draw-off point

230 V power cable with earthed plug

Splashproof to IP 24 D



<b>Type</b>			
Type	SNU 5 SL 1 kW	SNU 5 SLi	UFP 5 t SLi
Part no.	221116	221121	222176
Connection output	1 kW	2 kW	2 kW
Height	421 mm	421 mm	418 mm
Width	263 mm	263 mm	252 mm
Depth	230 mm	230 mm	222 mm
<b>Specification</b>			
Rated capacity	5 l	5 l	5 l
Power connection	1/N/PE	1/N/PE	1/N/PE
Rated voltage	230 V	230 V	230 V
Standby power consumption/24 h	0,20 kWh	0,20 kWh	0,23 kWh
Colour	white	white	white
IP-Rating	IP24	IP24	IP24
Weight	3,20 kg	3,20 kg	3,10 kg